### Draft

# Pump Station S-525A Summary of Hydraulic Design Data

#### Revisions:

- 25 October 2000 Comments and concurrence on design, pump station capacity criteria revised.
- 2 October 2000 Original submission.

XY Coordinate<sup>1</sup> – 894020 733125

Location: Hillsboro Canal, approximately 3,400 feet east of S-39 spillway

Purpose/Operational Intent: Water Supply Deliveries, Non-Flood Control

- Pump station backpumps the Hillsboro Canal into the Hillsboro Impoundment north compartment.
- Capture available storm runoff from LWDD's E-1W-S, E-1 and E-2 via Hillsboro Canal.

Design Condition: Non-Flood Control 1500 cfs Seepage Control Required

Pump Station Capacity Criteria:

The design pump capacity allows for a greater than 70% capture rate of the historical basin runoff outflow to tide. The Hillsboro Canal requires enhancement from S525A to LWDD E-1 to accommodate this captured outflow from LWDD E-2 westward. The increase in pump rate from original design offsets the decreased storage volume of the Ag Reserve Impoundment as designed in the Selected Plan.

Number of Pumps Pump Mix Type and Size

 Diesel
 2 @ 550 cfs

 Diesel
 1 @ 250 cfs

 Electric
 2 @ 75 cfs

## Mix Criteria:

- The pump station will be 5 bays with 2 sets of matching pumps.
- Two electric pumps are provided for greater seepage control for higher average stages inside Imp.
- The pump mix allows for intermediate flow values while having duplicate pumps throughout the system.

Control	Remote by SCADA or Loca
Design Heads	0.00 fact
Normal (7.00 HW to 16.00 TW)	9.00 feet
Maximum (5.50 HW to 16.00 TW)	10.50 feet
Intake Water Surface Elevations	
Maximum Non-Pumping	10.50 ft-NGVD
Maximum Pumping Date of the second of the se	10.50 ft-NGVD
Start Pumping	7.70 ft-NGVD
Normal Drawdown	6.0 to 7.5 ft-NGVD
Minimum Drawdown	5.50 ft-NGVD
Minimum Non-Pumping	5.25 ft-NGVD
Channel Invert	-9.00 ft-NGVD
Discharge Water Surface Elevations	
Maximum Non-Pumping	19.00 ft-NGVD
Maximum Pumping	16.00 ft-NGVD
, ,	16.00 ft-NGVD
Normal Pumping	
Minimum Pumping	6.50 ft-NGVD
Minimum Non-Pumping	6.50 ft-NGVD
Channel Invert	4.00 ft-NGVD

### Notes:

- 1 XY coordinates system used is NAD 83, Florida east, state plane.
- All elevations are in feet, NGVD (National Geodetic Vertical Datum of 1929)
- Diesel generator is required for control station and electric pumps in cases of power outage.

Data Compiled from: S-39 TW records and WPA Alternative hydrograph evaluations.